

AGNI VIJAY

TOTAL FIRE SECURITY SOLUTIONS

An ISO Certified Company ISO 9001 : 2015, ISO 14001:2015, ISO 45001:2018
CE Standards | District Industries Centre (DIC) | Bhopal Municipal Corporation
Regd. MSME (Govt. of India & M.P. Govt.)



OUR SERVICES

- ✓ Fire Extinguishers
- ✓ Fire Hydrant Installation
- ✓ Fire Alarm Installation
- ✓ Annual Maintenance Contract
- ✓ Fire NOC (No Objection Certificate)
- ✓ Fire and Safety Audit
- ✓ Fire Safety Training
- ✓ Industrial Safety Equipment
- ✓ Road Safety Equipment
- ✓ Agriculture Digital Grain & Seed Moisture Meter

HEAD OFFICE

223, 2nd Floor, Shalimar Trade Center, Main
Bhopal Railway Station, Hamidia Road, Bhopal (M.P.)

OUR BRANCHES

BHOPAL, BETUL, ITARSI, PANDHURNA, NASRULLAGANJ, REWA, GANJ BASODA, MUNGAOLI



ABC STORED PRESSURE TYPE FIRE EXTINGUISHER



Suitable for classes 'A' 'B' 'C' the use of Multi Purpose dry powder fire extinguisher provides an ideal multipurpose unit to virtually all common fire risks and especially suited to paper, cloth etc. any electrical fire, LPG Gas, Liquid fires etc. such as chemicals, petroleum, oils, paints etc. Dry powder provides a swift fire fighting action and prevents the reigniting of flames, Dry Powder Fire Extinguishers are supplied in stored pressure type 1kg / 2kg 4kg / 6kg / 9kg confirming to IS 15683

DRY CHEMICAL POWDER CARTRIDGES TYPE FIRE EXTINGUISHER

Suitable for classes 'B' 'C' Fire the use of Multi Purpose dry powder fire extinguisher provides multipurpose unit for virtually all common fire risks and especially suited to paper, cloth or any electrical fire and LPG Gas, Liquid fires such as chemicals, petroleum, oils and paints. Dry powder provides a swift fire fighting action and prevents the reigniting of flames. Dry Powder Extinguishers are supplied in both cartridge-type 6kg / 9kg capacity fire extinguisher confirming to IS 15683.



DRY CHEMICAL POWDER TROLLEY MOUNTED TYPE FIRE EXTINGUISHER



Suitable for classes 'B' 'C' Fire the use of Multi Purpose dry powder fire extinguisher multipurpose unit for virtually all common fire risks and especially suited to paper, cloth or any electrical fire and LPG Gas, Liquid fires such as chemicals, petroleum, oils and paints. Dry powder provides a swift fire fighting action and prevents the re-ignition of flames. Dry Powder Extinguishers are supplied in cartridge-type 25kg / 50kg / 75 kg Capacity trolley mounted fire extinguisher confirming to IS 16018.

WATER CO₂ TROLLEY MOUNTED TYPE FIRE EXTINGUISHER

Suitable for class 'A' fire. The use of the water type extinguishers an ideal unit virtually for all common fire risks and especially suited to paper, textile cloths, wood furniture and timber shops, Department Stores, Hospitals, Educational institutions, Ware Houses etc. Water type extinguishers are supplied in both cartridge type and stored pressure type 9 ltrs. Capacity fire extinguishers confirming to IS 15683 & 45 ltrs. Capacity trolley mounted fire extinguishers Confirming to IS 16018





MECHANICAL FOAM TROLLEY MOUNTED TYPE FIRE EXTINGUISHER



Suitable for class 'A' and 'B' fires. The use of AFFF foam extinguishers provides an ideal solution for almost all common fire risks and is especially suited for flammable fires such as paint, petroleum, oils, etc. The blanket effect of AFFF foam provides swift fire-fighting action and prevents re-ignition of flammable vapors. Foam extinguishers are available in both cartridge and stored-pressure types (9 liters). Capacity fire extinguisher conforms to IS 15683. Trolley-mounted fire extinguisher (45 liters) conforms to IS 16018.

CO₂ GAS TYPE FIRE EXTINGUISHER

Suitable for classes 'B' and 'C' fires. The use of carbon dioxide (CO₂) extinguishers provides an ideal solution for fire risks and is especially suited to electrical fires and flammable materials such as petroleum products and flammable gases like LPG, propane, and butane. The effect of CO₂ provides a swift cooling action and prevents the re-ignition of flammable vapors. CO₂ extinguishers are available in 2 kg, 3.2 kg, and 4.5 kg sizes, conforming to IS 15683.



CO₂ GAS TROLLEY MOUNTED TYPE FIRE EXTINGUISHER



Suitable for classes 'B' and 'C' fires. The use of carbon dioxide (CO₂) extinguishers provides an ideal solution for fire risks and is especially suited to electrical fires and flammable materials such as petroleum products and flammable gases like LPG, propane, and butane. CO₂ provides a swift cooling action and prevents the re-ignition of flammable vapors. These extinguishers are available in trolley-mounted units of 6.5 kg, 9 kg, and 22.5 kg, conforming to IS 16018.

MODULAR TYPE FIRE EXTINGUISHER

Contents: Automatic ABC/BC Dry Chemical Powder, FM-200, Clean Agent, etc.
Operation: Activates automatically when heat reaches a preset temperature (57°C to 140°C) via a fusible link—no external power required.
Application: Ideal for storage areas and general spaces such as workshops, offices, garages, showrooms, libraries, and areas storing flammable liquids, gases, or chemicals. Available in Capacity: 2kgs, 5kgs, 10kgs



FIRE EXTINGUISHERS SPARE PARTS

					
Valve	Pressure Gauge	Siphon tube	Hose	Valve O-ring	Spindle
					
Spindle O-ring	Bottom	Belt	Nozzle	Safety pin	Label
					
Powder	Wall clamp	Cap	Hose	Wheel	CO2 cartridge
					
DCP Nozzle	CO2 hose	CO2 horn	CO2 handle	CO2 Valve	Fire Hook
					
Hose	Nozzle	CO2 Valve Wheel	Hose	Floor Stand	Fire Bucket
					
Wall Stand	Fire Beater	Fire hook	Fireman Axe	Fire Blanket	Foam Refill

FIRE HYDRANTS



Single Hydrant Valve

Single headed S.S. ISI marked oblique pattern hydrant landing valve of 80 mm diameter, flanged inlet & 63mm diameter instantaneous type female outlet, complete as per IS:5290-1983 (Type 'A').



First Aid Hose Reel Drum

First-aid fire hose reel, wall-mounted swinging type complete with drum bracket, 25 mm diameter type complete with drum, bracket & 20 mm diameter, 36 m long high-pressure braided hose reel tubing as per (IS:444) with gun-metal shut-off nozzle having 25 mm diameter orifice.



RRL Hose with couplings

RRL Type- "A" ISI marked 63 mm x 15 mtr long complete with instantaneous type S.S. 63 mm diameter male & female couplings bound and riveted to hose pipe with copper rivets & 1.5 mm GI wire



Short Branch Pipe Nozzle

Branch pipe with nozzle in gun-metal / S.S. / Aluminum 63 mm diameter, short branch pipe with 16 mm diameter, nozzles ISI marked (IS:903)



Way Fire Brigade Inlet - 63 mm

S.S fire brigade connection (Suction collection head) consisting of 63 mm diameter, instantaneous type of coupling with built-in check valve & 150 m.m diameter, two-way



Way Fire Brigade Inlet - 63 mm

S.S fire brigade connection (Suction collection head) consisting of 63 mm diameter, instantaneous type of coupling with built-in check valve & 150 m.m diameter, three-way



Fire Single Door Hose Box

- Material: Mild Steel
- Usage: Fire Fighting
- Door Type: Single Door with Locking Arrangement
- Coating: Red Epoxy Powder Coated
- Color: Red



Double Door Hose box

- Material: Mild Steel
- Usage: Fire Fighting
- Door Type: Double Door with Locking Arrangement
- Coating: Red Epoxy Powder Coated
- Color: Red



Butterfly Valve

Cast iron gear/hand lever operated multi purpose soft seated water butterfly valve having centric disc construction one piece body with vitriolic seat PN.16 rating, SS-304 shaft, complete



Non-Return Valve

C.I. water-type non-return valve suitable for pressure 15kg /sqm complete as required conforming to IS:776 Class-II



Pressure Gauge

Pressure gauge 100mm with accessories (Make: Guru / Deafness / Fiebig) and shall include stopcock and all fittings.



Pressure Switch

Pressure switch Make: Indofos / Deafness



Auto Panel

Suitable for operation on 415V, 3 phases, 50HZ AC supply with enclosure protection class IP42, complete as per specifications. Starter, meter, selector switches, indicating LED with terminal facilities for repeated audio-visual indicators at terrace level & remote push button for ON/OFF operation in fire control room











Fire Fighting Pump

A fire-fighting pump is a centrifugal pump which is used for pumping fire-fighting water. Fire-fighting pumps can be designed for transportable use (e. g. on fire-fighting vehicles or as portable fire pumps) or for stationary use (e.g., hydrants, sprinkler systems).

FIRE BRANCHES AND NOZZLES

					
Hand control branch	Triple Purpose	FB-10 X	FB-5 X	Instantaneous Adaptor	Instantaneous Adaptor
					
Collecting Breeching	Long Branch Pipe	Triple Purpose	Navy Diffuser	Navy Diffuser Mini	Portable Spray Nozzle
					
Hand Controlled Jet & Spray	Jumbo Curtain Nozzle	3-Position Nozzle	Combat Nozzle	Fog Nozzle	Revolving Branch Pipe
					
Hose Reel Nozzle	Air Release Valve	Alarm Check Valve	Pressure Restricting Valve	High Velocity Spray Nozzles (UL Listed)	Inline Inductor
					
Variable Inline Inductor	Medium Expansion Foam Generator	Hi-Expansion Foam Generator (MK2)	FRP Tank Mobile Foam Unit	Water Jet Monitor	Fire Vehicle Pumps-Normal Pressure Series
					
Portable Fire Pump-NFF 1300	Manual Hose Binding Machine	Fire Bell	Fire Sprinkler Pendant	Fire Sprinkler Pendant	Flexible Sprinkler Drop Hose

			
Aqueous Film Forming Foam 3	Fire Ball	Fireman Axe	Breathing Apparatus BA Set
			
Fire Fighting Uniform	Fire Fighting Suits	Safety Hand Lamp LED	Safety Hand Lamp LED

FIRE ALARM SYSTEMS

			
Fire Alarm Panel	Smoke Detector	Digital Manual Call Point	Fire Alarm Hooter with Flasher
			
Fire Alarm Hooter	Fire Alarm Hooter with MCP	Fire Alarm Hooter ABS	Response Indicator
		 2 Core 1.5 sq mm Fire Alarm Armoured Cable	 Conventional Fire Alarm System Wiring and Connection Diagram
Integrated Fire Alarm with Public Address System	Fire Alarm Cables	Fire Alarm Cables	Fire Alarm System Conventional Wiring Diagram



Since-2007

AGNI VIJAY

TOTAL FIRE SECURITY SOLUTIONS

HEAD OFFICE :

223, 2nd Floor, Shalimar Trade Center, Main Bhopal
Railway Station, Hamidia Road, Bhopal (M.P.)

☎ 99938 39448, 9926 331175

✉ agni_vijay@yahoo.com | 🌐 www.agnivijay.com

OUR BRANCHES

**BHOPAL, BETUL, ITARSI, PANDHURNA, NASRULLAGANJ,
REWA, GANJ BASODA, MUNGAOLI**



Since-2007

